

VILLAGE OF LITTLE CHUTE

ORDINANCE NO. 2, SERIES OF 2011

AN ORDINANCE AMENDING THE VILLAGE OF LITTLE CHUTE MUNICIPAL CODE SECTION 16-102 FINANCE AND TAXATION - MINI-STORM SEWERS/STORM SEWER LATERALS, SECTION 34-2 PUBLIC UTILITIES - MINI- STORM SEWERS/STORM SEWER LATERALS, SECTION 34-128(f) PUBLIC UTILITIES - SUMP PUMP DISCHARGE REGULATED, AND SECTION 42-134(d)(3) SUBDIVISION REGULATIONS - DRAINAGE SYSTEMS – DRAINAGE SYSTEM REQUIREMENTS – SUMP PUMP CONNECTION REQUIREMENT

BE IT ORDAINED by the Village Board of Trustees, Village of Little Chute, Outagamie County, Wisconsin as follows:

Section I. Chapter 16- Section 102 Finance and Taxation – Mini-Storm Sewers/Storm Sewer Laterals, Chapter 34 Public Utilities, Section 2 - Mini-Storm Sewers/Storm Sewer Laterals and Section 128(f) - Sump Pump Discharge Regulated and Chapter 42 Subdivision Regulations Section 134 - Drainage Systems (d)(3) Drainage System Requirements – Sump Pump Connection Requirement of the Village of Little Chute Code of Ordinances are amended as follows.

Sec. 16-102. Mini-storm sewers/storm sewer laterals.

Mini-storm sewer/storm sewer laterals shall be assessed pursuant to ~~section 34-2~~ the Village of Little Chute's Mini Storm Sewer/Storm Sewer Lateral Policy.

Sec. 34-2. Mini-storm sewers/storm sewer laterals.

(a) A mini storm sewer shall consist of a six inch pipe placed under ground located in the terrace area of the road right-of-way. In line wyes shall be provided for the connection of sump pumps from two or more separate structures.

(b) A storm sewer lateral shall consist of a minimum four inch diameter pipe constructed to connect directly to the storm sewer main by the use of an in-line wye. The lateral shall serve a single structure.

(c) Whenever any mini-storm sewer/storm sewer lateral project is constructed by the village, for the purpose of requiring abutting property owners to hook up sump pump discharges, underground, from building structures directly to the mini-storm sewer/storm sewer lateral, then each abutting property owner immediately following completion of construction of the mini-storm sewer/storm sewer laterals project shall be required to so hook up existing sump pump discharge line within ~~30~~ 45 days directly from the abutting structure underground to the mini-storm sewer/storm sewer lateral. This shall be the same requirement for installation and connection of sump pump discharges to mini-storm sewers/storm sewer lateral as appears in chapter ~~36~~ 42, subdivision regulations, the terms and conditions of which are incorporated herein. The cost of such project shall be apportioned. ~~All storm sewers or mini storm sewers shall be constructed within either the road right of way or the road right of way terrace as determined from time to time by the village board.~~ No downspouts shall be connected to a storm sewer lateral ~~the mini storm sewer~~, except with permission of the building inspector for hazard mitigation and it shall be limited to one. There shall be no downspouts connected to a mini storm sewer.

Sec. 34-128. Sump pump discharge regulated.

(f) Connection order; extensions. A connection order may be served, in person or by certified first class mail, upon either the owner of the property or its occupant. The order shall provide that, unless an appeal from the order is timely filed, connection to the storm sewer shall be made within 45 days after its issuance. Upon issuing such an order, the building inspector shall promptly file a copy thereof with the village clerk. Upon reasonable written request made by the owner, time extensions may be granted for ordered connections at the discretion of the building inspector.

Sec. 42-134. Drainage system.

(3) *Sump pump connection requirement.* Each owner of a platted lot where storm sewer laterals have been installed or will be installed in the future pursuant to village ordinance shall be required, at the time of construction or thereafter, to connect the building sump pump outlet directly to the storm sewer lateral as installed at the time of the plat approval by the subdivider or as subsequently installed by the village pursuant to this section or any other ordinance of the village. It shall be the responsibility of the person taking out a building permit to see that the sump pump discharged from the building constructed upon the property is installed underground from the building and connected to the storm sewer laterals. In addition, it shall be the responsibility of the owners of existing buildings where mini-storm sewers/storm sewer laterals are installed hereinafter by the village to connect all ~~see that the property owner's sump pump discharges from the building as previously constructed upon the property is installed or reinstalled underground from the building and connected to the mini-storm sewer/storm sewer lateral. No downspouts shall be connected to the storm sewer lateral, except with the permission of the building inspector for hazard mitigation and it shall be limited to one. There shall be no downspouts connected to a mini storm sewer.~~

Section II: Severability. If any provision of this Ordinance is invalid or unconstitutional, or if the application of this ordinance to any person or circumstances is invalid or unconstitutional, such invalidity or unconstitutionality shall not affect the above provisions or applications of this Ordinance which can be given effect without the invalid or unconstitutional provisions or its applications.

Section III: Effective Date. This Ordinance shall become effective on the date of passage and posting or publication.

Date introduced: December 8, 2010

Approved and adopted: January 5, 2011

VILLAGE OF LITTLE CHUTE

By: _____

Charles Fischer, Village President

Attest:

Vicki Schneider, Village Clerk